
ROBOSLIDETM RESIDENTIAL SLIDE GATE OPERATOR

Dimensions



Mechanical Specifications

| MOTOR | 12V DC, 7-amp battery |
|-------------------------|---|
| CYCLES | Capable of 70 cycles per day with plug-in transformer. Cycles with solar power varies. Contact manufacturer. |
| CAPABILITIES | Maximum gate length 20'. Maximum gate weight 800 lbs. |
| GATE TRAVELING SPEED | 11" per second |
| SHIPPING WEIGHT | 104 lbs. |
| POWER FAILURE | The unit is equipped with a battery backup system (50 cycles). |
| COVER | Heavy-duty, weatherproof polyethylene plastic cover. |
| CHASSIS | Constructed with 1/8" metal that is welded and gold zinc-plated. |

Electrical Specifications

| COUPLING | Coupling gives smooth operation to the gate. |
|----------|--|
| ALARM | Activates anytime the moving gate is physically stopped by an obstruction. |
| TIMER | Can be set from 0-60 seconds. |
| SENSOR | If the gate hits a vehicle while closing, it reverses. If it hits a vehicle while opening, it stops, reverses several inches, and stops again. |


3-Year Warranty

THE CHAMBERLAIN GROUP, INC.
845 Larch Avenue • Elmhurst, IL 60126

www.chamberlain.com

©2004 The Chamberlain Group, Inc. Printed in U.S.A., 12/04 ELGBRRLO ROBOSLIDETM
RESIDENTIAL SLIDE
GATE OPERATOR





ELITE TO THE TAXABLE PROPERTY OF THE PROPERTY



RoboSlide™

Engineered for easier installation and enhanced operation.

The RoboSlide™ is our most advanced slide gate operator for single family residences. Designed for super-quiet and reliable performance, it can handle up to 70 cycles per day with gates weighing up to 800 lbs. and up to 20 feet in length.

Plus, what makes this system truly unique is its long list of built-in safety and convenience features. To simplify installation, the operator may be installed with low-cost, low-voltage wiring or in remote locations using our optional "Solar 3" 12-volt power system. It is also equipped with an automatic closing timer, safety reversing sensor, electronic shutoff and may be set up with an optional safety loop system.

Built-in strength, safety and convenience features

Elite™ operators are skillfully crafted in every detail. Each model features the most advanced and most complete list of components available in the industry.



Motor
Permanent magnetic
12-volt DC motor.



Surge Suppressor
Surge suppressor module
protects the RoboSlide™
from near lightning strikes.

Reversing Sensor

and stops again.



BatterySealed 12-volt, 7-amp
battery for long
operational life.



If the gate hits a vehicle while closing, it reverses. If it hits a vehicle while opening, it stops, reverses several inches,



Gear Box 30-to-1 ratio gear reducer in an oil bath.



Alarm Indicator
Alarm will sound anytime the moving gate is physically stopped by an unwanted object.



Control Board

Modular control board uses LEDs
to indicate all input and output
functions of the operator.



Optional Solar Panel
Allows RoboSlide™ to operate
in remote locations.