

RAMSET GATE OPENERS

QUICK REFERENCE GUIDE



	SLIDE					SWING				OVERHEAD							
	Residential	Res/Com	Com/Industrial	Com/Industrial	Com/Industrial	Residential	Commercial	Com/Industrial	Com/Industrial	Com/Industrial							
	RAM 50 UL	RAM 100 UL	RAM 1000 UL	RAM 5500 UL	RAM 5000 UL	RAM 30 UL	RAM 300 UL	RAM 3000 UL	RAM 30 30 UL	RAM 2000 UL							
MAX. GATE SIZE & WEIGHT:	18' @ 700 lbs.	20' @ 700 lbs.	35' @ 1000 lbs.	45' @ 1500 lbs.	40' @ 1000 lbs.	12' @ 400 lbs.	18' @ 1000 lbs.	22' @ 800 lbs.	20' @ 3000 lbs.	20' @ 450 lbs.							
GATE SPEED OPENING:	1' / sec.	1' / sec.	1' / sec.	1' / sec.	1' / sec.	90° / 14 sec.	90° / 14 sec.	90° / 20 sec.	90° / 16 sec.	90° / 14 sec.							
CYCLES:	30 per hour	Continuous	Continuous	Continuous	Continuous	30 per hour	Continuous	Continuous	Continuous	Continuous							
MOTOR:	1/2 Hp 120 VAC 5.2 amp 50/60Hz.	1/2 Hp 120 VAC 4.5 amp 50/60Hz.	1/2 Hp 120 VAC 4.5 amp 50/60Hz.	3/4 Hp 120 VAC 8.5 amp 50/60Hz.	1/2 Hp 120 VAC 4.5 amp 50/60Hz.	1/2 Hp 120 VAC 5.2 amp 50/60Hz.	1/2 Hp 120 VAC 4.5 amp 50/60Hz.	1/2 Hp 120 VAC 4.5 amp 50/60Hz.	3/4 or 1 Hp 115 - 220 VAC 8.5 - 4.5 amp 50/60Hz.	1/2 Hp 120 VAC 4.5 amp 50/60Hz.							
OPERATING TEMPERATURE:		-10° F to 160° F.	-10° F to 160° F.	-10° F to 160° F.	-10° F to 160° F.		-10° F to 160° F.	-10° F to 160° F.	-10° F to 160° F.	-10° F to 160° F.							
OVERALL DIMENSIONS:	H 22" L 14 1/2" W 15"	H 22" L 14 1/2" W 15"	H 26" L 16" W 16 1/2"	H 26" L 16" W 16 1/2"	H 25" L 18 1/2" W 16 1/2"	H 20" L 13 1/2" W 13 1/2"	H 27" L 20" W 15"	H 28 1/2" L 23" W 18"	H 27 1/2" L 23 1/2" W 17 1/2"	H 10" L 143" W 13"							
SHIPPING WEIGHT:	75 lbs.	110 lbs.	125 lbs.	135 lbs.	150 lbs.	75 lbs.	110 lbs.	150 lbs.	200 lbs.	135 lbs.							
EMERGENCY RELEASE:	(C)	(A)	(A)	(A)	(D)	(B)	(A)	(B)	(B)	(E)							
OPTIONAL ACCESSORIES:																	
Battery Back-up System	N/A	N/A	Optional	Optional	Optional	N/A	Optional	Optional	Optional	Optional							
Power Inverter	Optional	Optional	Optional	N/A	Optional	Optional	Optional	Optional	N/A	Optional							
EMERGENCY RELEASE OPTIONS:	<p>A) Exclusive foot pedal release disengages gate from motor so it can be opened manually.</p> <p>B) By hand lever release.</p> <p>C) The gate can be pushed open when power is lost.</p> <p>D) Manual chain release.</p> <p>E) Pull out release disengages gate from motor so it can be opened manually.</p>					<p>(No power inverter option) RAM 5100 UL MAX. GATE SIZE & WEIGHT: 40' @ 2000 lbs. MOTOR: 3/4 Hp 120VAC 8.5 amp 50/60Hz.</p> <p>(No power inverter option) RAM 5200 UL MAX. GATE SIZE & WEIGHT: 40' @ 3000 lbs MOTOR: 1 Hp 220VAC 4.5 amp 50/60Hz.</p>				<p>(No power inverter option) RAM 3100 UL MAX. GATE SIZE & WEIGHT: 22' @ 1200 lbs. MOTOR: 3/4 Hp 120VAC 8.5 amp 50/60Hz.</p> <p>(No power inverter option) RAM 3200 UL MAX. GATE SIZE & WEIGHT: 22' @ 1200 lbs. MOTOR: 1 Hp 220VAC 4.5 amp 50/60Hz.</p>				<p>(No power inverter option) RAM 2100 UL MAX. GATE SIZE & WEIGHT: 20' @ 700 lbs. MOTOR: 3/4 Hp 120VAC 8.5 amp 50/60Hz.</p> <p>(No power inverter option) RAM 2200 UL MAX. GATE SIZE & WEIGHT: 20' @ 700 lbs. MOTOR: 1 Hp 220VAC 4.5 amp 50/60Hz.</p>			

DEALER SUPPORT • EASY INSTALLATION • HEAVY DUTY • RELIABLE • LOW MAINTENANCE • UP TO 10 YEAR WARRANTY