

# THE NEW

2200<sub>LBS</sub> CAPACITY

# VIKING

ACCESS SYSTEMS™



RESIDENTIAL AND COMMERCIAL

## SLIDE GATE OPERATOR

CLASS I, CLASS II, CLASS III, AND CLASS IV VEHICULAR GATE OPERATOR





### VIKING BLUE TECHNOLOGY

- Plug & Play connection for "Viking Blue" add-on products
- Viking Blue – Wireless Master/Slave Kit provides secure and reliable wireless communication
- Viking Blue – Wireless Diagnostic Tool provides diagnostic information within range of the Control Board



### BATTERY BACKUP

- Standard Battery Backup provides 100 continuous cycles at 100% duty cycle
- With Vikings "True" Battery Backup System batteries are not used during normal operation, maximizing battery life.

### VIKING RF-Link

- Plug & Play connection for "Viking RF-Link" add-on.
- Wireless Master/Slave communication using a robust bi-directional radio signal.



### LIGHTNING PROTECTION

- Advanced lightning strike protection up to 20,000 volts / 10,000 Amps.
- On board surge protection monitoring



- Plug & Play connection for "Viking Wifi" add-on
- Remote access to the control board settings, programming, operator diagnostics, gate controls and gate status all from the convenience of a computer or any compatible handheld device.



### SOLAR SMART

- Power Saving technology minimizes current draw while at standby.
- New solar enabled feature to maximize operation time

- Plug & Play connection for the "Viking Cell" add-on
- Cellular access to the control board settings, programming, operator diagnostics, gate controls and gate status. Informs user when failure has occurred. For multiple monitored operators, an optional GPS Locator provides the operator location.



### DIAGNOSTICS DISPLAY

- On-board LCD Monitor displays voltages, amps, gate status and diagnostics.



### DIGITAL LIMITS

- Simple, push button limit setup
- Adaptive Digital Limit control maintains open and close limit position during changing environments power failures.



New "VFLEX" Control Board

Built in heater  
- 20 F operation

Multi-layer Corrosion Protection

- G90 Galvanized
- Clear Zinc Plating
- UV rated Powder coating

Efficient 1 HP  
DC Motor

Conveniently located Manual  
Release and Reset Switches

New re-designed chassis  
Post Mount Ready

Convenient J-Box for  
high voltage wiring

Integrated Modular Power Box

- Convenient Fuse Access
- LED status indicators
- Convenient Power Switch
- E-Z Access Power Outlet
- E-Z Set-up 115V/230V

Motor	... 24 VDC 1 HP
Operating Speed	... 12 inches per second
Duty Cycle	... 100%
Battery Backup	... 100 Cycles
Power Source Options:	... 115V/230V AC single Phase ... 24V AC/DC (Included Power Supply)
Operating Temp.	... -20°F to 158°F



**7 YEAR RESIDENTIAL / 5 YEAR COMMERCIAL WARRANTY**

[www.vikingaccess.com](http://www.vikingaccess.com) - 800 908 0884