



residential and commercial

SWING GATE OPERATOR

Class I, Class II, Class III, and Class IV Vehicular Gate Operator

400 CYCLES
in case of power failure*

**WATER RESISTANT
GEAR HEAD UNIT**

Single stage, efficient
gearing system



Configurable to
open left or open right

Key for
manual release

Internal parts are
made of aluminum, stainless
steel and plated steel.

Powerful
and efficient
DC brush motor
in direct-drive configuration

**STAINLESS
STEEL
CASING
AVAILABLE**

The answer for an elegant solution for access control is fulfilled with the i-8 gate operator. The discreteness of the installation, the flexibility of operation, the efficiency of automation, and the adaptability of integration makes the i-8 gate operator a perfect solution in situations where aesthetics are required to satisfy the most exquisite taste.

Operational Specifications

Operation	24 VDC with 1/2 H.P. Motor
Main Power Source	120 / 220 VAC Single Phase
Battery	7 AmpHr 12 VDC x 2
Max Gate Weight	650 lbs.
Max Gate Length	12 Feet
Max Operating Speed	13-15 seconds per 90°
* Battery Backup Operation	400 Full Cycles (500 lbs. / 12' gate)
Max Duty Cycle	100%
Operating Temperature	-4°F to +158°F

WARRANTY
3 years residential
2 years commercial



vikingaccess.com

800.908.0884